

# VE-I Platform and Catalog Instrumentation

## Viewline GPS Speedometer



- Customer Group
  - Marine boat builder, panel builder and distribution
- Benefits and Features
  - Speed signal from built in antenna or NMEA 2K network
  - LCD readout for compass, time, distance and signal strength
  - Displays in MPH, Kn or KM/H
  - Speed variants for power and sail boats
- Technical Data
  - 12V
  - 110mm installation diameter
  - Operating temperature -20°C to +85°C
  - IP67 front, IPx2 rear
- Variants
  - Customer specific capable

Viewline GPS Speedometer



Availability: In stock, Allentown PA

# VE-I Platform and Catalog Instrumentation

## Viewline GPS Speedometer



### NMEA 2000 compatible:

The instrument will provide the following information:

|   |            |                         |
|---|------------|-------------------------|
| 1 | PGN 129025 | Position, rapid update  |
| 2 | PGN 129026 | COG & SOG, rapid update |
| 3 | PGN 129033 | Time & Date (time only) |
| 4 | PGN 060928 | ISO address claim       |

| Part Number   | Range              | Packing | MOQ |
|---------------|--------------------|---------|-----|
| A2C59501829   | 35 Kn / MPH / km/h | Bulk    | 10  |
| A2C59501830   | 70 Kn / MPH / km/h | Bulk    | 10  |
| A2C94723700-S | 35 Kn / MPH / km/h | Single  | 1   |
| A2C94723500-S | 70 Kn / MPH / km/h | Single  | 1   |
| A2C59501987   | 12 Kn / MPH / km/h | Single  | 1   |

### Viewline GPS Speedometer



Availability: In stock, Allentown PA



VDO / Marine  
Confidential

VDO